

# Hulk®

## Hulk Cross-Coupling Cable Protectors

### Benefits:

- Improved design built to take a beating
  - Withstand tremendous impacts without shattering
  - Beveled shape deflects load
- Quick & easy installation, reducing rig time
- No loose parts to drop downhole
- Grips tubing to prevent rotation
- Secures & protects ESP cable at coupling
- Built for multiple reruns
- Replaces banding near joints
- Eliminates cleanouts for bands

### Features:

- Premium annealed ductile iron
- Heavy duty cable guard with multiple capillary tube slots
- Shifts tubing string away from casing
- Captive Class 10.9 bolts (Grade 8)
- No-slip grip
  - Improved rotational and axial grip
- Single assembly design
  - Robust
  - No loose parts
  - Rapid installation

Product	Tubing	Cable Thickness	Capillary
Hulk 1.0	2 7/8" EUE	0.55" +/- 0.02"	1/4 & 3/8
Hulk 2.0	2 7/8" EUE	0.59" +/- 0.02"	1/4 & 3/8
Hulk 3.0	2 7/8" EUE	0.63" +/- 0.02"	1/4 & 3/8

### Applications:

- ESP cable protection
  - Deviated or inclined wells
- Unconventional horizontals – high DLS and tangents
- Chemical treatment with cap tube
- Protects gauge line
- 7" well casing



oiltoolsolutions.com

307.699.3198

\* ISO9001 Manufactured  
Third-Party Tested

